

产品特点 Material & Characteristic


- 铝合金压铸构成灯具主体,表面经防腐蚀静电喷涂处理, 持久耐用。
- 反射照明灯罩,间接照明、低眩光、光线均匀、柔和。
- 采用平面钢化玻璃透光,透光性强。
- 开启方便,便于更换光源和日常维护。
- 安装管径: Φ60-90mm。
- 安装高度: 3-4m。
- Main body cast by aluminum alloy, outside disposal with anti corrosive static electricity plastic-spur, perdurable.
- Lamp-chimney of reflective lighting, in directive lighting, low dazzle, symmetrical and soft light.
- Adopt transparency with plane-toughened glass, good transparency.
- Convenient for opening, changing of illuminant and repairing.
- Fixing caliber \$60~90mm.
- Fixing height: 4~5m.

应用范围 Applications

林荫、道路、公园、广场、庭院、步行街等场所。

Path, road along river, park, square, courtyard, commercial area etc.

产品尺寸 size







技术参数 Product Parameter			65
型号 Model	光源/灯功率 lamp	灯头 Base	电压/频率 Voltage & frequency
HQBN-70L/TY05	MH 70W	E27/Rx7s	220V/50Hz
HQBN-150L/TY05	MH 150W	E27/Rx7s	220V/50Hz